CERTIFICATE OF COMPLIANCE

Certificate Number E467949

Report Reference E467949-2021-03-31

Date 2021-April-19

Issued to: Quintex GmbH

i_Park Tauberfranken 13 Lauda-Koenigshofen97922 DE

This is to certify that representative samples of

SEALING BUSHINGS FOR USE IN ZONE CLASSIFIED HAZARDOUS LOCATIONS - COMPONENT

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: See next page for Standards for Safety.

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.





CERTIFICATE OF COMPLIANCE

Certificate Number E467949

Report Reference E467949-2021-03-31

Date 2021-April-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Models:

Line bushings for use in Class I, Zone 1, AEx db eb IIC Gb, Zone 21, AEx tb IIIC Db; Ex db eb IIC Gb, Ex tb IIIC Db Hazardous Locations.

Type LB followed by S or U; followed by M or N; followed 10, 12, 16, 20, 21, 24, 25, 27, 30, 32, 33, 36, 38, 40, 41, or 42; followed by 0, 1, 2, 3, 4, or 5; followed by a two digit number from 00 to 50.

Line bushings for use in Class I, Zone 1, AEx db eb IIC Gb, Zone 21, AEx tb IIIC Db; Ex db eb IIC Gb, Ex tb IIIC Db Hazardous Locations.

Type LB followed by P or Z; followed by 1, 2, or 3; followed by 10, 12, 16, 20, 21, 24, 25, 27, 30, 32, 33, 36, 38, 40, 41, or 42; followed by 0, 1, 2, 3, 4, or 5; followed by a two digit number from 00 to 50.

Standards for Safety:

UL 60079-0, Explosive atmospheres – Part 0: Equipment – General requirements UL 60079-1, ELECTRICAL APPARATUS FOR EXPLOSIVE GAS ATMOSPHERES - PART 1: FLAMEPROOF ENCLOSURES "D"

UL 60079-7, Explosive atmospheres — Part 7: Equipment protection by increased safety "e" UL 60079-31, Explosive atmospheres — Part 31: Equipment dust ignition protection by enclosure "t" CAN/CSA C22.2 No. 60079-0, Explosive atmospheres — Part 0: Equipment — General requirements CAN/CSA C22.2 No. 60079-1, ELECTRICAL APPARATUS FOR EXPLOSIVE GAS ATMOSPHERES - PART 1: FLAMEPROOF ENCLOSURES "D"

CAN/CSA C22.2 No. 60079-7, Explosive atmospheres — Part 7: Equipment protection by increased safety "e"

CAN/CSA C22.2 No. 60079-31, Explosive atmospheres — Part 31: Equipment dust ignition protection by enclosure "t"



