

IAL3SK1 (F)

Termination Set in shrink-technology for non-hazardous area.

Termination Set non-Ex

- Compact design
- Temperature resistant up to 130°C (IAL3SK1 F 120°C)
- Easy and fast to assemble
- Applicable for different heating tapes CLD; ILL; ILMP; ILH (up to 120°C)
- Different sets separately available

Description

The IAL3SK1 is a termination set which is easy and fast to assemble. The heating tape will be connected with the feeding cable by using a ceramic terminal block and afterwards overshrunk with a special shrink tubing. Because of the illustrated instruction manual the installation is very easy and requires no special tools.



Specification

Max. ambient temperature:	130°C or 120°C for IAL3SK1 F
Usable for following heating tapes:	CLD, ILL, ILMP, ILH
Cross section:	up to 2,5mm ²
Length connection side:	120mm
Length end seal:	58mm

Further information

Please consult the termination instructions!

Order information

Part number:	
IAL3SK1:	Power connection and end seal in one kit For heating tapes with polyolefin jacket
IAL3SK1 F:	Power connection and end seal in one kit For heating tapes with fluoropolymer jacket

Alternative products

Pat number:	
IAL5SS:	Non-Ex Termination set in screw technology

Additional products

Part number:	
IAL3VK1:	Connection set (Heating tape-Heating tape)
IAL3AG1:	Power connection and end seal for direct entry in a special enclosure
AG 101:	Non-Ex glasfibre reinforced polyester enclosure for up to 3 heating circuits

