



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

| | | | |
|---------------------|---|--|--|
| Certificate No.: | IECEx EPS 16.0046 | Page 1 of 4 | <u>Certificate history:</u> |
| Status: | Current | Issue No: 2 | Issue 1 (2020-01-07) Issue 0 (2016-06-27) |
| Date of Issue: | 2025-11-27 | | |
| Applicant: | Quintex GmbH i_Park Tauberfranken 13 D-97922 Lauda-Königshofen Germany | | |
| Equipment: | Signal tower type QA-0191-0150-4_/_/_/_ / _/_/_/_ , LED-Matrix-Display type QA-0191-0150-4_/_/_/_ D / _/_/_/_ | | |
| Optional accessory: | | | |
| Type of Protection: | "db", "tb" | | |
| Marking: | for QA-0191-0150-4_/_/_/_ / _/_/_/_ Ex db IIC T6/T5 Gb Ex tb IIIC T120°C Db | for QA-0191-0150-4_/_/_/_ D / _/_/_/_ Ex db op is IIB T4 Gb Ex tb op is IIIC T120°C Db | |

Approved for issue on behalf of the IECEx
Certification Body:

Position:

Signature:
(for printed version)

Date:
(for printed version)



1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

Bureau Veritas Consumer Products Services Germany GmbH
Businesspark A96
86842 Türkheim
Germany





IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 16.0046**

Page 2 of 4

Date of issue: 2025-11-27

Issue No: 2

Manufacturer: **Quintex GmbH**
i_Park Tauberfranken 13
D-97922 Lauda-Königshofen
Germany

Manufacturing locations: **Quintex GmbH**
i_Park Tauberfranken 13
D-97922 Lauda-Königshofen
Germany

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-1:2014 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

IEC 60079-28:2015 Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation
Edition:2

IEC 60079-31:2022 Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure "t"
Edition:3.0

This Certificate **does not** indicate compliance with safety and performance requirements
other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[DE/EPS/ExTR16.0046/02](#)

Quality Assessment Report:

[DE/EPS/QAR11.0001/15](#)



IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 16.0046**

Page 3 of 4

Date of issue: 2025-11-27

Issue No: 2

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

Flameproof signal towers can be operated in hazardous areas of zone 1 or 2 (gas group IIA, IIB, IIC, temperature class T5 and T6) or in zone 21 or 22, dust group IIIC, T120 °C. The flameproof LED-Matrix-Displays can be operated in hazardous areas of zone 1 or 2 (gas group IIA, IIB, temperature class T4) or in zone 21 or 22, dust group IIIC, T120 °C. Both versions consist of a flameproof and dustproof enclosure „Ex-d“ in which signal modules are installed. For connecting there are Ex cable glands or line bushings available which are approved for hazardous areas.

Max. ambient temperature: -40 °C to +60 °C (Ex-d signal tower)

-20 °C to +40 °C (LED-Matrix-Display QX-VisuEx)

Rated Voltage 5 - 265V AC/DC

Maximum power input: 28 W (Ex-d signal tower in different versions),

72 W (QX-VisuEx)

SPECIFIC CONDITIONS OF USE: NO



IECEx Certificate of Conformity

Certificate No.: **IECEx EPS 16.0046**

Page 4 of 4

Date of issue: 2025-11-27

Issue No: 2

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Addition of different LED tower lamps Werma and Patlite.